Technical Data

Scotchgard™ Resilient Floor Protector

Description

The Scotchgard™ Resilient Floor Protector is a high performance protective floor coating for vinyl tile and vinyl sheet flooring that utilizes multiple polymer technologies to produce a hard surface that is resistant to scratches, stains, and scuff marks.

Special Features

- Glossy, hard surface is resistant to soiling
- Suitable for multiple substrates: VCT, vinyl tile, luxury vinyl tile, linoleum, and asphalt tile floors
- No stripping required
- Spot repairable
- Scotchgard[™] Resilient Floor Protector is compatible with conventional floor finish and may be used as a top coat
- Scotchgard™ Resilient Floor Protector is not intended for use on asbestos containing flooring materials. Ensure that the flooring you are working on does not contain asbestos.

Applications

- Education
- Health Care
- Retail
- Office

Packaging

3.785 liter bag

2 bags per case

Approximate coverage rate is 2000 square feet per gallon.

General Use Directions

Refer to Tech Bulletin "3M™ Resilient Floor Protection System" for specific use instructions.

Product Information:

(Typical Values)

- 1. pH: 7.4 8.4
- 2. Flash Point: non-flammable
- 3. Solubility in Water: complete
- 4. Specific Gravity: ~1.03
- 5. Appearance: white liquid
- 6. VOC < 1% weight
- 7. Boiling Point > 95 °F
- 8. Viscosity < 8 centipoise
- 9. Percent Solids ~ 22
- Slip Resistance: Meets or exceeds ASTM D2047-82 coefficient of friction 0.5 (James Machine)

NOTE:

Refer to product Material Safety Data Sheet for specific physical properties, health hazard, first aid and precautionary information.

Scotchgard™ Resilient Floor Protector MSDS:

31-1076-4



3M Branch Sales Offices

ANCHORAGE

11151 Calaska Circle Anchorage, AK 99515

Telephone: 907/522-5200 Facsimile 907/522-1645

HONOLULU

4443 Malaai Street Honolulu, HI 96818 Mail to: P.O. Box 30048 Honolulu, HI 96820

Telephone: 808/422-2721 Facsimile 808/422-9557

CONTINENTAL UNITED STATES

Customer Service Department 3M Center Building 223-5S-07 St. Paul, MN 55144-1000

Order Entry 1-800-852-9722 Facsimile 1-800-447-0408

CANADA

N6A 4T1

1840 Oxford Street East London, Ontario, Canada N5V 3G2 Mail to: P.O. Box 5757 London, Ontario, Canada

Telephone: 800/364-3577 Facsimile: 800/479-4453

Important Notice to User

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application

Warranty and Limited Remedy: 3M warrants that each 3M product will be free from defects in material and manufacture for 90 days from the date of purchase from 3M's authorized distributor. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.

