

Scotch-Brite™ Surface Preparation Pad

Technical Data

June 2009

Description:

Scotch-Brite™ Surface Preparation Pad prepares floors for finish applications. Scuffs surface to create optimal bonding of finish. Diffuses scratches and conforms to uneven surfaces. Use with water-based or oil-based finishes.

Special Features:

- Coated with specialized abrasive for rapid, smooth cutting of floor finish
- Used with water or neutral cleaner instead of harsh stripping chemicals
- Provides medium level stripping to prepare floor for additional coats of finish
- No slippery residue from strippers
- No stripper cleanup on baseboards or nearby floors
- No user exposure to stripping chemicals; no stripping chemical residue on clothes and shoes

Applications:

For use on finish-coated flooring such as wood, vinyl tile, sheet vinyl, marble, terrazzo or concrete.

Packaging and Markings:

Pads are maroon with 3M SPP marked on one side. Cases hold 10 pads each with the exception of the smallest (8") rounds which are 25/case.

General Use Directions:

1. Scotch-Brite™ Surface Preparation Pad can be run on auto-scrubbers, swing machines or rectangular floor machines
2. Use Scotch-Brite™ Surface Preparation Pad with 3M™ Neutral Cleaner Concentrate 3* or 3M™ Neutral Cleaner LO Concentrate 33* or with water
3. A flexible backer floor pad, such as the 3M™ White Super Polish Pad 4100 can be used to hold the Scotch-Brite™ Surface Preparation Pad
4. After scrubbing, rinse floor with water
5. Once floor is dry, dust with 3M™ Easy Trap Duster
6. Apply new coats of floor finish

The Scotch-Brite™ Surface Prep Pad is designed to be used on both sides with pads typically being flipped to the second side after approximately 5000 square feet of use in wet applications.

*Concentrated product to be diluted and dispensed using the 3M™ Twist 'n Fill™ Cleaning Chemical Management System

Product Specifications:

(Typical Values)

1. Outer Diameter: Designated size +/- 1/16"
2. Center Hole Diameter 3 ¼" except for smallest (8") pads which have a 2 ¾" center hole
3. Thickness: 0.4 inches
4. Fiber Type: Nylon
5. Tensile Strength: 30 lbs/2 in
6. Aggressiveness: Schiefer Cut of 4g

Pad Cleaning:

If pads can not be rinsed right away, pads should be placed in a plastic liner after use to prevent finish residue from drying onto pad before rinsing. Pad may be rinsed under a faucet or with a hose. A pressure spray nozzle will remove residue most effectively. Hang pads vertically to dry.

Safety:



User is solely responsible for determining whether the Scotch-Brite™ Surface Preparation Pad is suitable for user's flooring and method of application. Some floors may release dust that could be hazardous to the user or bystanders. Eye, Skin and/or respiratory personal protection equipment may be appropriate to reduce the risks associated with exposure to airborne dust.

3M Branch Sales Offices

ANCHORAGE

11151 Calaska Circle
Anchorage, AK 99515
Telephone: 907/522-5200
Facsimile: 907/522-1645

HONOLULU

4443 Malaai Street
Honolulu, HI 96818
Mail to: P.O. Box 30048
Honolulu, HI 96820
Telephone: 808/422-2721
Facsimile: 808/422-9557

CONTINENTAL UNITED STATES

Customer Service Department
3M Center Building 223-2N-21
St. Paul, MN 55144-1000
Order Entry: 1-800-852-9722
Facsimile: 1-800-447-0408

CANADA

1840 Oxford Street East
London, Ontario, N5V 3G2
Canada
Telephone: 519/451-2500
Facsimile: 519/452-6262

Important:

The information provided in this report is believed to be reliable; however, due to the wide variety of intervening factors, 3M does not warrant that the results will necessarily be obtained. All details concerning product specifications and terms of sale are available from 3M.



Building and Commercial Services Division
St. Paul, MN 55144-1000
1-800-852-9722
www.3M.com/commcare

3M, Scotch-Brite and Twist 'n Fill are trademarks of 3M.

© 3M 2009. All rights reserved.
07/09 DMR #592873