


## Brush and Pad selection

A full range of brush and pad drive systems are available for both models in order to provide the correct specification for the type of floor to be maintained. All brushes are fully interchangeable and can be varied to suit changing conditions or a change in location.




50cm PadLoc pad drive system



55cm Heavy duty scrubbing brush



55cm Light duty scrubbing brush



55cm Long life scrubbing brush



55cm Long life light duty scrubbing brush

## TTB Specifications

Model	Brush Motor	Vac Motor	Power	Run Time	Recharge Time	Pad/Brush width	Capacity	Weight	Drive Speed	Brush Speed	Dimensions WxLxH
TTB6055	400W	400W	2x12V (24v 100Ah)	2.25Hrs	4hrs	50/55cm	60L	158Kg	-	100rpm	550x1280x1160mm
TTB6055T	400W	400W	2x12V (24v 100Ah)	2.25Hrs	4hrs	50/55cm	60L	158Kg	4.2Kph	100rpm	550x1280x1160mm

# TTB6055

A Better TwinTec... By Design



[www.numatic.co.uk](http://www.numatic.co.uk)



[www.numatic.de](http://www.numatic.de)



[www.numatic.ch](http://www.numatic.ch)



[www.numatic.fr](http://www.numatic.fr)



[www.numatic.nl](http://www.numatic.nl)



[www.numatic.co.za](http://www.numatic.co.za)

Numatic International Limited, Chard, Somerset, TA20 2GB Tel: 01460 68600 Fax: 01460 68458

Numatic International Limited 2012. Specification subject to change without prior notice. PN:244123

# Power and performance where it's needed

*Two new models to compliment the range of popular FloorCare products. Just as much cleaning performance with a larger capacity for longer duty or larger floors areas.*

## TTB6055, TTB6055T



TTB6055T



Flexifill 1m filling hose



Plug-in charger system



Traction wheels TTB6055T only

The 55cm (20") size of TwinTec is becoming more and more popular and, in support of this, we have introduced two new models with 60 litre capacity, a 50% increase over the 40 litre models and available in both traction and non-traction specifications.

Both models of TTB-6055 have 60 litre capacity and a 55cm (20") single brush scrubbing path, dual brush pressure selection, built in battery charging, easy fill and easy emptying facilities, with added traction power drive for the 6055T model which would be essential if inclines or ramps are involved.

In terms of operation the Nutronic control system provides for individual speed and water flow rate settings with additional Hi-Lo selection for use in more sensitive areas.

***The 6055 models with or without traction power drive will provide a standard of cleaning performance and operation that satisfies all operators.***

Simple to use Nutronic control panel  
TTB6055T shown



2x Fully sealed gel batteries